



11kW 16Amp 3 Phase

Monitored PDU (3 Phase)

Model Number
IPMTJ-2103-516



Meter True RMS Current Meter,

Power Monitor Total Power Monitoring by Meter, Web, SNMP, Free Bundle Software

Protocols Http, Https, SNMP, DHCP, UDP, SSL(verified by IE6 on WinXP)

Alarm Thresholds User-Defined Alarm Thresholds for Warning and Overload

Event Alert Email, Trap, Audible Alarm

Temp./Humidity Option Accessory

General

Output	(21) IEC 320 C13 (3) IEC 320 C19
Input	(1) IEC 309 with 3m
Protection	(3) 16 Amp breaker

Communication

SSL Indication	(1) Yellow LED
DHCP Indication	(1) Green LED
Circuit Status	(3) Red LED
Network	(1) RJ45 for Ethernet
Temp./Humidity	(1) RJ11 for ENV probe connection
PDU ID	1 Digits Seven Segment for PDU Identification
Current Meter	3 Digits Seven Segments for True RMS Meter Range: 0A ~ 20 A Resolution: 0.1A Precision: +/-2%/+/-0.1AMP

Operation

Nominal Voltage	400V AC, 3-Phase 3P+N+PE
Voltage	230V
Frequency	50/60HZ full range
Load Capacity	11.1 kVA
Max. Input Current	16 Amp
Max. Output Current (Outlet)	IEC 320 C13: 10A IEC 320 C19: 16A
Max. Output Current (Bank)	16 Amp
Temperature	0 ~ 40 Celsius degree
Humidity	0% ~ 90%
Size	56 x 1645 x 44 mm
Weight	4.9 kg

Regulatory Approvals

