



16Amp 230V

Switched PDU

Model Number
IPSWV-1314-1620



- Meter** True RMS Current Meter,
- Power Monitor** Total Power Monitoring by Meter, Web, SNMP, Free Bundle Software
- Protocols** Http, Https, SNMP, DHCP, UDP, SSL(verified by IE6 on WinXP)
- Outlet Control** Individual,
- Power Delay** Power On/Off Sequence can be Defined
- Alarm Thresholds** User-Defined Alarm Thresholds for Warning and Overload
- Event Alert** Email, Trap, Audible Alarm

General Output	(14) IEC320 C13 (2) C19
Input	(1) IEC320 C20 Inlet; Enclosed IEC320 C19 to C20 Power Cord 3 Meters long
Protection	(1) 16 AMP Circuit Breaker
Communication	
SSL Indication	(1) Yellow LED
DHCP Indication	(1) Green LED
Output Status	(16) Green LED
Network	(1) RJ45 for Ethernet
Current Meter	3 Digits Seven Segments for True RMS Meter Range: 0A ~ 20 A Resolution: 0.1A Precision: +/-2%/+/-0.1AMP

Operation	
Nominal Voltage	230V
Voltage	200V~ 240V full range
Frequency	50/60HZ full range
Max. Output Current	16 Amp (UL derated 12 Amp)
Temperature	0 ~ 40 Celsius degree
Humidity	0% ~ 90%
Size	56 x 1245 x 44 mm
Weight	3 kg

Regulatory Approvals UL 60950-1, UL Listed, CSA, cUL Listed, CB by UL
CE, EN 55022 Class A, EN 55024, EN 61000-3-2, EN 61000-3-3
C-Tick AS/NZS CISPR 22: 2006

