



2x16Amp 230V

Switched PDU

Model Number

IPSWS-3988-1622



Meter True RMS Current Meter.

Power Monitor Total Power Monitoring by Meter, Web, SNMP, Free Bundle Software

Protocols Http, Https, SNMP, DHCP, UDP, SSL(verified by IE6 on WinXP)

Alarm Thresholds User-Defined Alarm Thresholds for Warning and Overload

Event Alert Email, Trap, Audible Alarm

Temp./Humidity Option Accessory

General

Output	(8) IEC320 C13 (8) IEC320 C19
Input	(2) IEC320 C20 Inlet; Enclosed IEC320 C19 to C20 Power Cord 3 Meters long
Protection	(2) 16 AMP Circuit Breaker

Communication

SSL Indication	(1) Yellow LED
DHCP Indication	(1) Green LED
Circuit Status	(2) Red LED
Output Status	(16) Green LED
Network	(1) RJ45 for Ethernet
Temp./Humidity	(1) RJ11 for ENV probe connection
PDU ID	1 Digits Seven Segment for PDU Circuit Identification
Current Meter	3 Digits Seven Segments for True RMS Meter Range: 0A ~ 20 A Resolution: 0.1A Precision: +/-2% +/-0.1AMP

Operation

Nominal Voltage	230V
Voltage	200V~ 240V full range
Frequency	50/60HZ full range
Max. Output Current	16 Amp for Each Branch
Temperature	0 ~ 40 Celsius degree
Humidity	0% ~ 90%
Size	215 x 432 x 44 mm
Weight	6 kg

Regulatory Approvals

