



10Amp 230V

Switched PDU

Model Number
IPSWB-1308-1014



- Meter** True RMS Current Meter,
- Power Monitor** Total Power Monitoring by Meter, Web, SNMP, Free Bundle Software
- Protocols** Http, Https, SNMP, DHCP, UDP, SSL(verified by IE6 on WinXP)
- Outlet Control** Individual,
- Power Delay** Power On/Off Sequence can be Defined
- Alarm Thresholds** User-Defined Alarm Thresholds for Warning and Overload
- Event Alert** Email, Trap, Audible Alarm

General

Output	(8) IEC320 C13
Input	(1) IEC320 C20 Inlet; Enclosed IEC320 C19 to C14 Power Cord 3 Meters long
Protection	(1) 10 AMP Circuit Breaker

Communication

SSL Indication	(1) Yellow LED
DHCP Indication	(1) Green LED
Output Status	(8) Green LED
Network	(1) RJ45 for Ethernet
Current Meter	3 Digits Seven Segments for True RMS Meter Range: 0A ~ 20 A Resolution: 0.1A Precision: +/-2%/+/-0.1AMP

Operation

Nominal Voltage	230V
Voltage	200V~ 240V full range
Frequency	50/60HZ full range
Max. Output Current	10 Amp
Temperature	0 ~ 40 Celsius degree
Humidity	0% ~ 90%
Size	90 x 432 x 44 mm
Weight	3 kg

Regulatory Approvals

CE, EN 55022 Class A, EN 55024, EN 61000-3-2, EN 61000-3-3
C-Tick AS/NZS CISPR 22: 2006

